




SPES

Una facility di "medio termine"
per fasci radioattivi
ai Laboratori Nazionali di Legnaro

The ISOL concept for RIB production






Laboratori Nazionali di Legnaro



ISOL facilities nel mondo


	Fascio primario	Potenza sul bersaglio	Fissioni al secondo
ISOLDE (CERN)	protoni 1 GeV, 2 μ A	0.4 KW	10^{12}
HRIBF (USA)	protoni 40 MeV, 10 μ A	0.4 KW	10^{11}
TRIUMF(CANADA)	protoni 450 MeV, 100 μ A	25 KW	
EXCYTE (Catania)	^{12}C 45A MeV ^{13}C 45A MeV	0.4 KW 18 W	Fascio prodotto $1.5 \cdot 10^4$ ^8Li
SPIRAL2 (Francia)	deutoni 40 MeV, 5 mA	200 KW	10^{13}
SPES (LNL)	protoni 40 MeV, 200 μ A	8 KW	10^{13}

Evolution of the ORNL DT Approach



- Total of 1200 hours operation with 10-12 μ A of 42 MeV protons
- More than 120 different radioactive beams extracted
- 400 W deposited in target (power density is 97 W/g, as LNL-project)

ORNL is an ideal test-bench for the LNL multi-slice target




Area per le nuove installazioni

This is an aerial photograph of a large industrial complex, likely a particle accelerator facility. The image shows several large, rectangular industrial buildings with flat roofs. A river or canal flows through the upper left portion of the image. A white line is drawn across the top of the image, enclosing a green field area. The text 'Area per le nuove installazioni' is written in white, slanted font within this enclosed area. Other labels are placed on specific buildings: 'Exp halls' on two separate buildings, 'ALPI Linac' on a long building, and 'Tandem' on another building. The facility is surrounded by green fields and some trees, with a road and other smaller buildings visible on the right side.

Exp
halls

ALPI Linac

Exp
halls
Tandem



1-step vs 2-step


1-step: p 40 MeV 200 μ A on multi-slice direct target (60gr UCx)

2-step: d 40 MeV 5mA on thick ^{12}C converter + UCx target (800 gr)


10^{13} fissions/sec

Release times considered:
1-step 2 sec, 2-step 40 sec

In-target production



Intensities after acceleration




Evaluated beam intensities

Beam evaluated with the following efficiencies

1+ 30%, n+ 5%, acc. 50% = 0.75%

1+ 90%, n+ 12%, acc. 50% = 5.4% Xe, Kr



SPES-DirectTarget: Strategic Plan

DRIVER

40 MeV,
200 μ A
protons

ISOL RIB SOURCE

RIB production and selection (The core of the machine): Target, +1 source, Charge breeder, Isotope Separator, Authorization

RI Beam Accelerator

ALPI is ideal for the re-acceleration of RIBs. Its features determine the type of Physics with RIBs at LNL

EXPERIMENT

INFN-LNL
+
NFN sections /Labs
+
...

Direct Target Development

Computing (Thermo-mechanical, Diffusion-Effusion, on-target production...)

INFN-LNL
ENEA-Bo
Uni-PD Mech

Pellet (LaC-SiC-UCx pellets, binder materials, Carbide Foam...)

Prototype (Full engineering, Test of the P-dissipation, Test of C-window, ...)

Uni-PD, Chem & Mech Eng


INFN-LNL & LNS, Material Res. Lab (UniPD-LN)

Agreement with
ORNL being signed




SPES-Direct Target Work Package Structure

Hypothesis: to be defined asap (before fall)



Organizzazione dei LNL e Servizi

Progetto SPES_DT



Servizi critici:

- Servizio BersaglioDiretto
- Servizio Dosimetria
- Servizio Edilizia
- Servizio sicurezze
- Controlli

Necessaria una Analisi delle attività e una riorganizzazione dei servizi


Sistemi di controllo

Vuoto

Criogenia


Proton Injector: the original layout

Cavity developments going on well,
but...still 2÷3 years R&D (couplers,
cryomodules, ...)



a quicker-to-build Driver is necessary

Two options for: 40 MeV, 200 μ A with little or no R&D




(the whole Linac can be bought turn-key from industry)


(being built for SPL, prototyped)

Being compared issues::

Beam Species, I, P_{beam},
 Beam Losses, Modularity, Possibility of Upgrade, (0.4-3 mA)
 Installed electrical P,
 Operation electrical P, Building Size/Cost, Accelerator Cost,
 Further R&D needed, Realization Time, Human Resources needed, Technological Maturity, Degree of possible Industry involvement



5 MeV
 30 m
 (50 Hz pulsed, 352 MHz, 5 2.5-m-long DTL units, $\beta = 0.09$ & 0.15 , 3 mA 1.5% duty cycle)
 to BNCT neutron source




Decision due by September 2006

SPL CDR2 Preliminary Layout 15.3.2005
 Work in progress!

The Proton Driver

DTL solution

	SPES	
proton energy	40 MeV	
rep rate	50 Hz	
peak current	30 mA	
pulse length	0.3 ms	
duty cycle	1.5%	
average current	0.45 mA	
beam power	18 kW	
RF peak power	5 MW	
mains power	0.15 MW	




Alternative solutions under consideration:
superconducting linac 352 MHz or 176 MHz



Final decision due in September 2006



The TRASCO Ion Source TRIPS (built by INFN-LNS)



Nominal current (**40 mA**) at low emittance (~ 0.1 mm mrad rms) has been measured (LNS)

The TRASCO-SPES RFQ

(TRASmutazione di SCORie)




Design @ LNL, Engineering and construction @ Industry
Brazing @ CERN, Measured by LNL at the company


1999-2002: 2 Modules (R&D TRASCO activity)

2004-2007: construction of modules 3÷6


2008: low-P tests of each module, high P test of the whole RFQ




Machining of 4-pole vanes



Assembly



Brazing



The measurement set-up

Preliminary shielding calculation for the driver linac



LABORATORI NAZIONALI DI LEGNARO

Service for all types of requests

ROUGH SHIELDING CALCULATIONS

• Lateral shielding (90°) of the LINAC tunnel in the following conditions
beam: protons

Energy: 40 MeV final

beam losses: 1 W/m continuous


target: Iron or copper

Desired RDAE: 0.1 $\mu\text{Sv/h}$


(90°)	SOURCE TERM (0°)	EFFECTIVE SOURCE TERMS
10 MeV	1.2×10^{-3} n/p	10^{-18} Sv/p at 1 m
20 MeV	4×10^{-3} n/p	10^{-17} Sv/p at 1 m
30 MeV	1.1×10^{-2} n/p	3×10^{-17} Sv/p at 1 m
40 MeV	2.3×10^{-2} n/p	3×10^{-17} Sv/p at 1 m

FOR THE DOSE EQUIVALENT RATE OUTSIDE A LATERAL SHIELD FROM A CONTINUOUS LOSS OF PROTONS ALONG A BEAM LINE EQUATION

For the 10–40 MeV sections, 90–130 cm of concrete is enough



Preparation of ALPI as a RNB Accelerator



ALPI Upgrade as a RIB Accelerator

- New or displaced HI Injector
- Full set (n.16) of low beta resonators at $> 6 \text{ MV/m}$
- Further upgrade of medium beta resonators ($4.3 \rightarrow 5.5 \text{ MV/m}$)
- Moderate upgrade of the cryogenics system (back to nominal 7 W/cavity)
- Some quads from 20 to 30 Tm
- New diagnostics (large I and E ranges, RA, sub mm spatial res., few 100 ps,...)

Schedule

	2006	2007	2008	2009	2010	2011	2012
Target prototypes							
Authorization to construction							
Facility Design							
Building Construction							
Completion of driver (1st part-RFQ)							
Installation and commissioning of SPES-1							
Construction of driver (2nd part-DTL)							
Installation and comm. of the full driver							
Installation and comm of the target system							
Alpi preparation for post acceleration							
Installation of RIBs transfer lines and spectrom.							
Complete commissioning							

Ansatz:

New TDR October 2006

Green light by the end of 2006

Energy profile following possible ALPI Upgrade (Ansatz: full funding today!)

Year		2006	2007	2008	2009
E_{acc} [MV/m]	CR03	0	0	6	6
	CR04->CR06	3	3,5	3,5	6
	CR07->CR20	3,6	3,6	4,2	5,5
Energy [MeV/A]	$^{238}\text{U}^{28+}$	4,96	5,21	5,84	8,64
	$^{132}\text{Xe}^{19+}$	6,13	6,39	7,15	10,27
	$^{132}\text{Xe}^{26+}$		9,6		13,2
Energy [MeV/A] with HE Stripper	$^{132}\text{Xe}^{40\div44+}$	9,1	10,6	11,25	15,1
	$^{132}\text{Xe}^{41\div45+}$		13	13.04	17.07

1. P_{cryo} /resonator back to nominal value (7 W)

2. Low-beta cavities: higher P amplifiers (3 → 3.5 MV/m)

3. Low-beta resonators: CR03 at 6 MV/m, CR04-CR06 3.5 → 6 MV/m

4. Further upgrade of medium beta resonators (4.3 → 5.5 MV/m)

5. Operation of the new ECR Ion Source

6. Use of high E stripper (~80% beam loss)

FUNDED

The resonator upgrades apply as well to ALPI as an RNB reaccelerator

Outlook

SPES was originally motivated by the appropriateness of ALPI as RNB Accelerator (Upgrade Programme started – partly funded)

The multislice DT concept allowed focusing onto a 40 MeV 200 μ A proton beam driver

Definition of industry-assisted 40 MeV p driver (nc or sc), by September 2006

Decision within 2006 → RNBs in 2012